

## Perlator®

### Laminar Stream - 1.5 gpm Flow Restricted Regular Size




flow, stop and go®

#### Features and Benefits

- ▶ Watercolours™ design: Color coding to identify flow rate and stream pattern.
- ▶ Patented construction provides a splash-free, crystal clear (non-aerated) stream.
- ▶ Recommended for use in healthcare facilities to prevent mixing air and water.
- ▶ Integrated anti-liming honeycomb replaces conventional wire mesh screens prone to lime build up.
- ▶ Anti-clogging dome screen filters sediment and particles.
- ▶ Compatible with regular and vandal proof M22 & M24 metric housings.
- ▶ Available housing finishes: chrome, polished brass, brushed nickel and oil rubbed bronze.
- ▶ Laser marked housings with statutory marks.

#### Certifications

ANSI/ NSF® -61-372  
ASME A112.18.1M and CSA B125  
Meets **CALGreen** requirements  
WaterSense



#### Thread & Part Number

Part #	Designation	Thread Size
TSL-150INST-N	Insert only	
TSL-150MST-N	Regular male	15/16"-27
TSL-150FST-N	Regular female	55/64"-27
TSL-150DTST-N	Regular dual thread	15/16"-27 x 55/64"-27
TSL-150MSTVP-N	Vandal proof regular male	15/16"-27
TSL-150FSTVP-N	Vandal proof regular female	55/64"-27
TSL-150DTSTVP-N	Vandal proof regular dual thread	15/16"-27 x 55/64"-27

#### Dimensions

No	mm	In
A	20.88	.822
B	12.00	.472
C	19.97	.786
D	≈ 13	≈ 1/2

Other product combinations available.

#### Packaging:

Inserts 1 pc (bag), 6 pcs (bag), 50 pcs (bag)  
Reg. male/female/dual thread 1 pc (bag), 6 pcs (tube), 50 pcs (tray)  
Reg. vandal proof male/female/dual thread 1 pc (bag), 6 pcs (tube), 40 pcs (tray)


#### Color Code

Dome	Ring	Basket
Green	Green	Light Gray

#### Housings



#### Flow Rate Curve



#### Technical Data

Materials: Body Acetal  
Washer EPDM

#### Continuous

max. 60 °C  
max. 140 °F

90psi max.  
6.2bar max.

#### Short-term (5 minutes max.) Per ASME A112.18.1 testing requirements.

max. 70 °C  
max. 160 °F

125psi max.  
8.5bar max.