

PCW



flow, stop and go®

PCW Shower Regulators - .35 to 2.5 gpm Flow Regulator - Pressure Compensating

Features and Benefits

Operates as a flexible orifice to provide reliable flow regulation from 20 to 80 psi.

Fits directly into any 1/2" threads.

Recommended for use with shower handles.

Fits within shower heads and hand held shower providing both flow control and seal.

Part Numbers				
Part #	Color	gpm	L/min	
FC-PCW-01-035	Brown	0.35	1.3	
FC-PCW-01-050	Lime Green	0.5	1.8	
FC-PCW-01-100	Blue	1.0	3.7	
FC-PCW-01-150	Green	1.5	5.7	
FC-PCW-01-175	Light Blue	1.75	6.6	
FC-PCW01-200	Lilac	2.0	7.6	
FC-PCW01-220	Yellow	2.0	8.3	
FC-PCW01-250	Black	2.5	8.3	

Pac	/20	in	~	ė
гас	nay	ш	ч	b

PCW shower regulator

1 pc (bag), 6 pcs (bag), 50 pcs (bag)



Certification

Materials		
Name	Material	
Washer	Silicone	
Core	Acetal	
O-ring	EPDM	

Technical Data

Medium:

Clear water only

Continuous Short-term (5 minutes max.) max. 50 122 or or 100psi 6.9bar max. or or 100psi 6.9bar max. or or 100psi 6.9bar max.

Dimensions

